



ACCORDING DIN 2270 FOR LEVER INDICATORS



WIRELESS HUB CONNECTION

WIRELESS HID USB HID

DIRECT TO ANY APP & OS

INDICATOR FOR 2D / PROBE/ANGLE

WIRELESS 10 MDS APP

FREE VERSIONS

DATA MET FUNCTIONS

<p>2.1113 1.00 1.50 2.00 1.4705 0 MENU 177</p> <p>ANALOG SCALE</p>	<p>L: 0.000 MENU 0.000 0.000 0.000 4.029mm 0 0 7N</p> <p>COLOR GO / NOGO</p>	<p>L: 0.000 MENU 0.000 0.000 0.000 4.029mm 0 0 7N</p> <p>COLOR MAX / MIN / RANGE</p>	<p>TIMER 0.000 sec RESET</p> <p>TIMER</p>	<p>Setting reply 1 Auto PRECISION Sensor 1 D = 1.000000</p> <p>TOUCH PROBE SETTINGS</p>	<p>Formula Ax²+Bx+C Set Argv</p> <p>FORMULA Ax²+Bx+C</p>
<p>14.1936 average: 5.7457 -0.0004 50 points 21</p> <p>GRAPHIC MODE 1D/2D</p>	<p>Stat All Mode 1: 12.009 2: 36.646 3: 29.090 4: 23.070 5: 56.624</p> <p>MEMORY 2000 values</p>	<p>Stat All Mode 5 5 5 2 Page 1/1</p> <p>FOLDERS mode</p>	<p>Statistics MAX: 59.9510 MIN: 6.0090 AVG: 21.1826 D: 204.9000</p> <p>MEMORY STATISTICS</p>	<p>Temp.com. Glass, Quartz, Mo 20.00 c° RES</p> <p>TEMPERATURE COMPENSATION</p>	<p>Menu OFF Memory OFF PIN: 0</p> <p>PASSWORD</p>
<p>Display Angle 270 Sleep OFF Touch OFF</p> <p>DISPLAY & ENERGY</p>	<p>Resolution X.000 mm Normal</p> <p>RESOLUTION, mm/inch</p>	<p>MDS MODE Ultra Power CLEAR</p> <p>WIRELESS to MDS app</p>	<p>HID MODE Eco Power CLEAR</p> <p>WIRELESS & USB HID</p>	<p>0 P 0.334 0 75.573 MENU 177</p> <p>HUB mode (2D, Probe)</p>	<p>MICROTECH MICRON CALIPER FW: 4.5.3 Op time: 0h Calibration 1.1.2025 MAC: F7:5B:B8:C0:95:88 MANUAL</p> <p>DEVICE INFO, UPDATE</p>



- Manual **DataMet** Vertical and Horizontal calibration stands for dial, digital and lever indicators
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting,
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))

HORIZONTAL INDICATOR CALIBRATION STAND

Item No	Range		Resol	Micrometer head		Calibrated device																		
				Range	Accur.	Non-Rotating	dial indicator (res 0,1mm)	dial indicator (res 0,01mm)	dial indicator (res 0,001mm)	digital indicator (res 0,01mm)	digital indicator (res 0,001mm)	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB
	mm	inch	mm	mm	µm																			
25111027	0-25	0-1"	0,0001	25	±1.2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
25111051	0-50	0-2"	0,0001	50	±1.8	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
25111057			0,0005	50	±2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

VERTICAL INDICATOR CALIBRATION STAND

Item No	Range		Resol	Micrometer head		Calibrated device																			
				Range	Accur.	Non-Rotating	dial indicator (res 0,1mm)	dial indicator (res 0,01mm)	dial indicator (res 0,001mm)	digital indicator (res 0,01mm)	digital indicator (res 0,001mm)	dial test indicator (res 0,01mm)	dial test indicator (res 0,001mm)	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS
	mm	inch	mm	mm	µm																				
25113050	0-50	0-2"	0,0001	50	±1.8	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
25113057			0,0005		±2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•



DataMet interface



CONNECTION possibilities



VIDEO

VERTICAL



VIDEO

HORIZONTAL



DOWNLOAD MDS app WINDOWS



DOWNLOAD MDS app iOS, MacOS




DOWNLOAD MDS app ANDROID



DELIVERY SET



OPTIONAL





WIRELESS HUB CONNECTION

INDICATOR FOR 2D / PROBE/ANGLE

WIRELESS HID USB HID

DIRECT TO ANY APP & OS

Windows iOS

WIRELESS TO MDS APP

FREE VERSIONS

Windows iOS

DATA MET FUNCTIONS

<p>ANALOG SCALE</p>	<p>COLOR GO / NOGO</p>	<p>COLOR MAX / MIN / RANGE</p>	<p>TIMER</p>	<p>TOUCH PROBE SETTINGS</p>	<p>FORMULA Ax^2+Bx+C</p>
<p>GRAPHIC MODE 1D/2D</p>	<p>MEMORY 2000 values</p>	<p>FOLDERS mode</p>	<p>MEMORY STATISTICS</p>	<p>TEMPERATURE COMPENSATION</p>	<p>PASSWORD</p>
<p>DISPLAY & ENERGY</p>	<p>RESOLUTION, mm/inch</p>	<p>WIRELESS to MDS app</p>	<p>WIRELESS & USB HID</p>	<p>HUB mode (2D, Probe)</p>	<p>DEVICE INFO, UPDATE</p>



- Manual **DataMet** Universal calibration stands for dial, digital indicators with 0.01mm resolution and bore gauges
- Measuring range up to 1000mm
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting,
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- **Calibration** certificate included (ISO17025 (Ilac MRA))

Item No	Calibrated devices	Range		Resol	Micrometer head		Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB		
					Range	Accur.															
		mm	inch	mm	mm	µm															
251113007	Indicators & Bore gauges	0-300	0-12"	0,0001	25	±2	•	•	•	•	•	•	•	•	•	•	•	•	•		
251115007		0-500	0-20"				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
251119007		0-1000	0-40"				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•



DELIVERY SET

<p>FREE VERSIONS OF MDS APP</p>	<p>USB DATA/CHARGING CABLE</p>	<p>CALIBRATION PROTOCOL</p>	<p>DataMet BUTTON</p>	<p>DataMet FOOTSWITCH</p>	<p>MDS DISPLAY UNIT</p>	<p>MDS SOFTWARE</p> <p>STANDARD MDS app</p>
---------------------------------	--------------------------------	-----------------------------	-----------------------	---------------------------	-------------------------	---